

WELL PANEL X

FEATURES

- A fully realized kit of (4) battery operated black IP65-rated panel style fixtures, with (40) RGB warm white LEDs and a beam angle of 10.8 degrees
- Charging case designed to charge with the lid closed to save warehouse space
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built-in battery charger allows fixture to operate while charging
- Built-in IP65 5-pin DMX in/out allows for wired data
- Built-in Seetronic IP65 PowerKon input/output
- Control over DMX, CRMX, RDM, or RF
- Easy connection to WELL CONNECT box and ConnectFX app
- Pressure equalizing M12 Gore valve
- Built-in safety cable attachment point
- Easy-to-read OLED display
- Built-in PWM adjustment
- Included RF remote
- Included 4 pack charging case



SPECIFICATIONS

OPTICAL

- Light Source: 40 LEDs (RGBWW) 13.2 W, (556 mA), 50,000 hours life expectancy
- Color Temperature (range): 2800 to 6500 K
- Installed optics: 11.6°
- Beam Angle: 21.4°
- Field Angle: 31.7°
- Lumens: 6865 lm (AC power)
- Illuminance: 4575 lux @ 5 m (AC power)
- Lumens: 6615 lm (OFF battery setting)
- Illuminance: 4269 lux @ 5 m (OFF battery setting)
- Lumens: 2886 lm (5-hour battery setting)
- Illuminance: 1867 lux @ 5 m (5-hour battery setting)
- Lumens: 1807 lm (8-hour battery setting)
- Illuminance: 1194 lux @ 5 m (8-hour battery setting)
- Lumens: 1189 lm (12-hour battery setting)
- Illuminance: 769 lux @ 5 m (12-hour battery setting)
- Lumens: 851 lm (18-hour battery setting)
- Illuminance: 548 lux @ 5 m (18-hour battery setting)
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000

DYNAMIC EFFECTS

- Dimmer: Electronic

- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

CONSTRUCTION / PHYSICAL

- Dimensions: 17.17 x 5.31 x 10.24 in (436 x 135 x 260 mm)
- Dimensions case: 36.4 x 20.7 x 21.5 in (925 x 525 x 545 mm)
- Weight: 20.8 lb (9.43 kg)
- Weight case: 184 lb (83.5 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input (fixture and charging case): Seetronic Powerkon IP65
- Power Output (fixture and charging case): Seetronic Powerkon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: RDM, CRMX, NFC, RF
- DMX Channels: 5,8,9,12,16 channels
- Modes/Personalities: 5 personalities (5Ch, 8Ch, 9Ch, 12 ch, 16 ch)
- Wireless WDMX "G" Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Single unit:
- Power Linking: 12 units @ 120 V; 21 units @ 208 V; 23 units @ 230 V
- Power and Current: 120 W, 0.99 A @ 120 V, 60 Hz
- Power and Current: 113 W, 0.56 A @ 208 V, 60 Hz
- Power and Current: 115 W, .0.51 A @ 230 V, 50 Hz
- 4 pack case:
- Power and Current: 550 W, 4.60A @ 120 V, 60 Hz
- Power and Current: 536 W, 2.62 A @ 208 V, 60 Hz
- Power and Current: 522 W, 2.31 A @ 230 V, 50 Hz
- 4 Pack Case Fuse – T6.3A. 250V

BATTERY

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 4 hours
- Battery Life: 5, 8, 12,18 hours
- Battery Power: 44.4 V, 6600 mAh

CERTIFICATIONS / QUALIFICATIONS

- CE, FCC, UKCA
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- (4) WELL PANEL X
- (1) 4 slot charging case
- (1) basic RF controller
- (4) Seetronic PowerKon IP 65 power cords
- (4) Omega Brackets
- (1) QRG

OPTIONAL ACCESSORIES

- Clamps: CTC-50HC, CTC-50G, CTC-50CBLK, CTC 50HCN, CTC-50HCNBLK
- 45° hard filter (sold in singles with frame)
- 60° hard filter (sold in singles with frame)
- 100° hard filter (sold in singles with frame)
- 10°x60° hard filter (sold in singles with frame)
- 30°x60° hard filter (sold in singles with frame)
- 60°x10° and 60°x40° soft filter (sold in 2 packs without frames)
- Empty filter frame for soft filters (sold in singles without filters)
- Riglink PowerKon Extension cables
- Rig Link 5 pin DMX Cables