



COLORDash Accent 5X IP

A compact, IP65-rated wash fixture powered by a single 40W hex-color RGBAW+UV LED for a tremendous punch of evenly mixed, saturated color.

Its palm-sized, weatherproof design and flicker-free output make it ideal for discreet, high-impact accent lighting in broadcast, event, and architectural applications.

- Hex-color (RGBWAUV) compact LED wash
- Extremely compact with excellent output and IP65-rated versatility
- Variable electronic dimmer (0–100%)
- Simple and complex DMX channel profiles with RDM for programming versatility
- Double-bracketed yoke doubles as floor stand
- Easy to use OLED digital display
- Replaceable filter for additional beam angles
- Built-in auto programs recalled via DMX or Master/Slave

SPECIFICATIONS

Optical

Light Source: 1 LED (Hex-color RGBWA+UV) 40 W, (950 mA), 50,000 hours life expectancy.

Beam Angle w/ filter: 21.5°

Field Angle w/ filter: 47.1°

Beam Angle w/o filter: 11.4°

Field Angle w/o filter: 20.4°

Lumens: w/o filter: 890 lm

Lumens: w/ filter: 733 lm

Illuminance (total) w/ filter: 126 lux @ 5 m

Illuminance (total) w/o filter: 618 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: Yes

Dim Modes: 5

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 7.24 x 5.70 x 3.46 in (184 x 145 x 88 mm)

Weight: 2.8 lb. (1.3 kg)

Exterior Color: Black

Connections

Power Connection: Edison plugs to hard-wired

Power Input: Hard-wired

Data Connectors: 5-pin XLR DMX input and output cable whips

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 6, 8, 9, 13 or 14

Modes/Personalities: 5 personalities (6, 8, 9, 13 or 14)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 44 W, 0.68 A @ 120 V, 60 Hz

Power and Current: 44 W, 0.48 A @ 208 V, 60 Hz

Power and Current: 43 W, 0.44 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, RoHS

IP Rating: IP65, temporary outdoor/wet use with pressure equalizing M6 GORE valve

Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

5-pin DMX Cables

What's Included

COLORDash™ Accent 5XIP

Frosted filter